

LASER RANGEFINDER SPECS

SKU	MAGNIFICATION	OBJECTIVE LENS DIAMETER	MAX REFLECTIVE RANGE (UP TO)	TREE RANGE (UP TO)	DEER RANGE (UP TO)	MIN RANGE	ACCURACY (@ 100 YARDS)	MAX ANGLE READING	LINEAR FIELD OF VIEW (@ 1000 YARDS)	ANGULAR FIELD OF VIEW	EYE RELIEF	LENGTH	HEIGHT	WIDTH	WEIGHT
Razor. HD 4000 GB															
LRF-252	7x	25mm	4000 yds.	2500 yds.	2200 yds.	5 yds.	+/- .5 yds.	+/- 89°	341'	6.5°	17.5mm	4.4"	3.2"	1.7"	10.1 oz.
Razor. HD 4000															
LRF-250	7x	25mm	4000 yds.	2500 yds.	2200 yds.	5 yds.	+/- .5 yds.	+/- 89°	341'	6.5°	17.5mm	4.4"	3.1"	1.7"	9.9 oz.
Viper. HD 3000															
LRF-VP3000	7x	25mm	3000 yds.	2300 yds.	2000 yds.	6 yds.	+/- 1 yd.	+/- 89°	314'	6.0°	15.5mm	4.2"	3.1"	1.7"	9.1 oz.
Diamondback. HD 2000															
LRF-DB2000	7x	24mm	2000 yds.	1800 yds.	1400 yds.	5 yds.	+/- 1 yd.	+/- 60°	335'	6.4°	16.0mm	4.1"	3.1"	1.8"	7.6 oz.
Crossfire. HD 1400															
LRF-CF1400	5x	21mm	1400 yds.	950 yds.	750 yds.	5 yds.	+/- 1 yd.	+/- 89°	367'	7.0°	16.0mm	4.0"	2.9"	1.3"	4.8 oz.
Triumph. HD 850															
LRF-TRI850	5x	21mm	850 yds.	500 yds.	350 yds.	6 yds.	+/- .5 yds.	+/- 89°	335'	6.4°	13.0mm	3.8"	3.1"	1.4"	4.6 oz.

LASER RANGEFINDING BINOCULAR SPECS

SKU	MAGNIFICATION X OBJECTIVE LENS DIAMETER	LINEAR FIELD OF VIEW (@ 1000 YARDS)	ANGULAR FIELD OF VIEW	CLOSE FOCUS	EYE RELIEF	INTERPUPILLARY DISTANCE	DIOPTER RANGE	MAX REFLECTIVE RANGE (UP TO)	TREE RANGE (UP TO)	DEER RANGE (UP TO)	MIN RANGE	HEIGHT	WIDTH	WEIGHT
Ranger. HD 3000														
LRF-RGR3000	10x42	335'	6.4°	6.0'	17.0mm	55mm - 74mm	+/- 3	3000 yds.	1800 yds.	1500 yds.	6 yds.	6.7"	5.1"	32.4 oz.

BALLISTIC LASER RANGEFINDING BINOCULAR SPECS

SKU	MAGNIFICATION X OBJECTIVE LENS DIAMETER	LINEAR FIELD OF VIEW (@ 1000 YARDS)	ANGULAR FIELD OF VIEW	CLOSE FOCUS	EYE RELIEF	INTERPUPILLARY DISTANCE	DIOPTER RANGE	MAX REFLECTIVE RANGE (UP TO)	TREE RANGE (UP TO)	DEER RANGE (UP TO)	MIN RANGE	HEIGHT	WIDTH	WEIGHT
Talon. HD 10K														
LRF-TLN1250	12x50	272'	5.2°	25.0'	18.5mm	58mm - 76mm	+/- 4	10,000 yds.	4200 yds.	2600 yds.	10 yds.	7.2"	5.6"	46.8 oz.
LRF-TLN1042	10x42	321'	6.1°	15.0'	18.5mm	58mm - 76mm	+/- 4	10,000 yds.	4000 yds.	2400 yds.	10 yds.	6.3"	5.5"	40.8 oz.

GOLF LASER RANGEFINDER SPECS

MAX FLAG LINEAR FIELD REFLECTIVE MIN ACCURACY MEASURING SKU MAGNIFICATION DISPLAY TYPE RANGE OF VIEW LENGTH HEIGHT WIDTH WEIGHT RANGE RANGE (@ 100 YARDS) TIME (UP TO) (@ 100 YARDS) (UP TO)

Anarch. Image Stabilized

LRF-ANARCH 6x Red Illuminated 1400 yds. 450 yds. 10 yds. +/- 1 yd. 31.8' 1 Second 4.2" 3.0" 1.6" 9.2 oz.

Blade. Slope

LRF-BLADE-S 6x Black LCD 1400 yds. 350 yds. 6 yds. +/- 1 yd. 37.6' 1 Second 3.9" 3.0" 1.5" 6.5 oz. **Blade.**

LRF-BLADE	6x	Black LCD	1400 yds.	350 yds.	6 yds.	+/- 1 yd.	37.6'	1 Second	3.9"	3.0"	1.5"	6.5 oz.
-----------	----	-----------	-----------	----------	--------	-----------	-------	----------	------	------	------	---------

