



PRECISION DIVING BOARD MOUNT

INSTALLATION INSTRUCTIONS

CAUTION: Ensure firearm is unloaded before making any modifications.

CAUTION: Ensure all screws are securely tightened to the recommended torque before shooting.

ATTENTION

All torque specs are given as inch-pounds (in-lbs) not foot-pounds.

If Your Riflescope is Mounted in Existing Vortex® Precision Riflescope Rings, Follow the Directions Provided Below:

1. Remove the top ring half from the front ring (closest to the objective bell).
2. Place the diving board onto the lower ring half.

CAUTION: Take care to ensure the front edge of the mounting surface is not contacting the objective bell.

3. Alternately tighten the ring screws to 18 in-lbs while maintaining even spacing between the diving board and lower ring half.

INSTALLATION INSTRUCTIONS

M-00340-0

CAUTION: Ensure firearm is unloaded before making any modifications.

CAUTION: Ensure all screws are securely tightened to the recommended torque before shooting.

ATTENTION

All torque specs are given as inch-pounds (in-lbs) not foot-pounds.

If Your Riflescope is Not Yet Mounted in Vortex® Precision Riflescope Rings, Follow the Directions Provided Below:

1. Remove the upper ring halves (keeping them paired as packaged) and place aside.
2. Loosen the base screws and fit the lower ring halves onto a Weaver® or Picatinny base.
3. Position to allow proper riflescope placement for eye relief and even spacing on the riflescope tube.
4. Individually tighten both base clamp screws while pressing the ring half down and forward toward the muzzle ensuring it is seated against a cross slot in the rail. Tighten base clamp screws to 45-50 in-lbs.
5. Place the riflescope onto the lower ring halves and loosely reattach the upper ring half to the lower ring half for the back ring set (furthest from the objective bell).
6. Place the diving board onto the front ring half (closest to the objective bell).

CAUTION: Take care to ensure the front edge of the mounting surface is not contacting the objective bell.

7. Slide and rotate the riflescope for proper head position, eye relief, and vertical reticle alignment.
8. With the riflescope properly positioned, alternately tighten the ring screws in a crisscross pattern. Tighten screws to 18 in-lbs while maintaining even spacing between the ring halves and diving board mount.